

# Plenum Multi-Conductor/Overall Shield w/Drain Wire

UL Listed NEC Type, CL3P or CMP  
 Bare Copper Stranded Conductors  
 Low Smoke PVC Insulation  
 Overall Foil Shield with Stranded TC Drain  
 Low smoke white PVC Jacket  
 Sequential Footmarks  
 Ripcord



Part #	# of Conductors	AWG Size/Stranding	NOM Insulation (Inches)	NOM Jacket (Inches)	NOM OD (Inches)
PC22-2C-PSH-WHT	2	22 (7x30)	0.008	0.015	0.12
PC20-2C-PSH-WHT	2	20 (7x28)	0.008	0.015	0.14
PC18-2C-PSH-WHT	2	18 (7x26)	0.009	0.015	0.16
PC16-2C-PSH-WHT	2	16 (19x26)	0.009	0.015	0.19
PC14-2C-PSH-WHT	2	14 (19x27)	0.01	0.015	0.22
PC22-3C-PSH-WHT	3	22 (7x30)	0.008	0.015	0.13
PC20-3C-PSH-WHT	3	20 (7x28)	0.008	0.015	0.15
PC18-3C-PSH-WHT	3	18 (7x26)	0.009	0.015	0.17
PC22-4C-PSH-WHT	4	22 (7x30)	0.008	0.015	0.14
PC18-4C-PSH-WHT	4	18 (7x26)	0.009	0.015	0.19
PC16-4C-PSH-WHT	4	16 (19x29)	0.009	0.015	0.22
PC14-4C-PSH-WHT	4	14 (19x27)	0.01	0.015	0.26
PC12-4C-PSH-WHT	4	12 (19x25)	0.01	0.015	0.28
PC22-6C-PSH-WHT	6	22 (7x30)	0.008	0.015	0.17
PC18-6C-PSH-WHT	6	18 (7x26)	0.009	0.015	0.23
PC22-8C-PSH-WHT	8	22 (7x30)	0.008	0.015	0.18
PC22-12C-PSH-WHT	12	22 (7x30)	0.008	0.015	0.22

Source : All Generic Suppliers

Packing : 300 meter / Bulk reels and custom packing

All above cables can be produced with colored jackets. Data grade available in these cables using Polyethylene or Polypropylene insulations.

Please contact us for any additional information

*Specifications subject to change*